AlertWave



VNS2263 - Wireless Two-Way Intercom Station





The VNS2263 Wireless Two-Way Intercom Station is designed to provide two-way communication for applications where the installation of traditional hard-wired intercom systems is impractical or too costly.

When the VNS2263 is used with a main wireless paging controller, such as the **VS4810**, two-way communication between the main paging controller and an intercom wall station (or emergency call box) becomes available. The main paging controller can also initiate one-way communication to a group of intercom wall stations.

The VNS2263 is controlled by the VNS2210 wireless audio/visual controller to provide simple, reliable and cost-effective alternative solutions to traditional wired intercom systems.

Key Features:

- Hands Free Two-Way Communication
- One-Way Group Communication
- Integrated Speaker and Microphone

Options, Accessories and Complementary Products:

| Part Number | Description |
|-------------|----------------------------------|
| VNS2210 | Wireless Audio/Visual Controller |
| | |

Specifications:

| Dimensions | 4.75" x 3.45" x 1.15" | Data Cable | 25', CAT-5 |
|-----------------------|---|------------------|---|
| Weight | 0.85 lbs. | Audio | Built-In Omni-Directional Microphone and Speaker |
| Material / Finish | ABS Plastic, Black Faceplate with White Trim Ring | Operation Modes | Main Paging Controller to Intercom Wall Station(s), Intercom Wall Station to Main Paging Controller, Main Paging Controller Monitoring Mode |
| Operating Temperature | 0° - 140°F | Limited Warranty | One Year Parts and Labor |

*Specifications Are Subject to Change Without Notification



877 918-7243 www.visiplex.com