



VP-210 - Two-Line Alphanumeric Pager



VP-LC-4

The **VP-210 Two-Line Alphanumeric Pager** is designed to accommodate a wide variety of paging applications and environments.

The VP-210 supports 6 activation codes (ID's) for individual activation or membership activation in 5 separate groups. Creating groups provides the ability to activate multiple devices using a single transmission from a main wireless paging controller, such as the **VS4800** or **VNS5100**.

The VP-210 includes a carrying case, lanyard and battery.

Key Features:

- Two-Line Alphanumeric Display Format
- Message Time Stamp
- Unread Message Reminder
- Low Battery Indication
- Adjustable LCD Contrast
- Backlight Display
- Out of Range Indication
- Date and Time Display
- Vibrate and Silent Modes

Options, Accessories and Complementary Products:

Part Number	Description
VP-LC-4	Leather Case for VP-4 and VP-210

Specifications:

Dimensions	2.8" x 1.9" x 0.7" (W x H x D)	Selectivity	Better than 65 db
Weight	1.6 oz.	Spurious Rejection	Better than 60 PPM
Power	One 1.5 V AAA Battery	Image Rejection	Better than 50 db
Color	Black	Stability	Better than 5 PPM
Operating Temperature	14° - 130°F	Frequency	VHF (148 - 174 MHz), UHF (400 - 470 MHz)
Humidity	0% - 95%, Non-Condensing	Paging Format	POCSAG, Narrow Band
Alert Level	Minimum 75 db	Data Baud Rate	512 or 1200 BPS
Display Format	Two Lines with up to 18 Characters Per Line	Receiver Sensitivity	7u V/M
Activation Codes	6	Limited Warranty	One Year Parts and Labor

*Specifications Are Subject to Change Without Notification

VISIPLEX

877 918-7243

www.visiplex.com