



## VS1800 Alarm Input Expansion Unit

The VS1800 is a compact alarm expansion unit, that provides hard-wired input monitoring information to PageLink's paging controllers. Each VS1800 can monitor up to 96 dry-contacts or voltage level inputs, while assigning a pre-programmed text message to each input. Up to eight VS1800's can be cascaded to provide the ability to monitor up to 960 alarm events.



- *Monitor dry contacts or voltage level inputs easily*
- *Built-in memory battery backup*
- *Two-line LCD Display*
- *Pre-programmed text messaging to each input*
- *Compact Design for Mobility*

### Specifications:

<b>Dimensions:</b>	9.7" wide x 2.4" high x 5.5" deep	<b>Alarm Input Type:</b>	Normally open or normally closed
<b>Weight:</b>	2 lb.	<b>Display:</b>	Two-Line green LCD display with backlit.
<b>Power input:</b>	90-250VAC 50/60Hz 40Watt	<b>Interface:</b>	RS-232 port for PC programming and an integrated handheld microphone.
<b>Operating Temperature:</b>	0° to 40°F	<b>Power:</b>	Operates from a 12V DC 3A, AC or car power adaptor.
<b>Humidity:</b>	10 to 65%	<b>Limited Warranty:</b>	One-year Parts and Labor
<b>Software:</b>	PC Windows based software package that is designed to program, control and backup the unit database.		
<b>Input Impedance:</b>	47K Ohm		