



WPT-EN1210C - Wireless 900 MHz Push Button Emergency Transmitter



WPA-1004 WPRP-EN5040

Key Features:

- One Pre-Programmed ID
- 300' - 1,000' Range (Increased Using Data Repeater)
- In-Wall Mount
- Long-life Single Lithium Battery
- Low Battery Alert
- Surface Mount Installation Option (Recommended)

The **WPT-EN1210C Wireless 900MHz Push Button Emergency Transmitter** is designed to be used with a main wireless paging controller, such as the **VS4810** or **VNS5100**. It is designed to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

When the WPT-EN1210C push button is pressed, an activation signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert according will be generated according to the programming.

The WPT-EN1210C can generate an automated message to report low battery status. In addition, the WPT-EN1210C offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device. The WPT-EN1210C includes a push button and mounting hardware.

***Note:** Compatible with WPR-EN4200 Wireless Receiver and WPRP-EN5040 Wireless Repeater Only.

An extra deep plastic single gang box is required for optimal signal coverage. Metal box not recommended.

Options, Accessories and Complementary Products:

Part Number	Description
WPRP-EN5040	Wireless 900 MHz Repeater (WPA-1002 is Required for Outdoor or Weather Resistant Installation)
WPA-1004	Extra Deep Plastic Box for Surface Mount Installation

Specifications:

Dimensions	3" x 4.6" x 3" (W x H x D). Cord length - 7'	Activation Type	Momentary Switch
Weight	0.85 lbs.	Programming	PC Based Programming Kit
Power	Single 3V Lithium Battery	Transmit Format	Multi-Channel Spread Spectrum
Color	White	Frequency Range	900 MHz
Operating Temperature	32° - 140°F	Activation Codes	1
Humidity	0% - 90%, Non-Condensing	Limited Warranty	One Year Parts and Labor

*Specifications Are Subject to Change Without Notification