



WPT-IR - Wireless UHF Infrared Pendant Transmitter



The **WPT-IR Wireless UHF Infrared Pendant Transmitter** is designed to send a pre-programmed text message to a designated pager or LED display.

When used with the **WPR-IR Pendant Location Transmitter**, the WPT-IR can provide location information in addition to a pre-programmed text message. When the button is pressed, the WPT-IR receives the Location ID information from a nearby WPR-IR. This ID is sent with the pre-programmed message to a designated pager or LED Display. When used with a main wireless paging controller, such as the **VNS5100**, the Location ID can be converted to a customized description.

When the WPT-IR and the WPR-IR are used with a main paging controller, the pendant's message content can be used to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail or telephone subscribers.

In this configuration, when the WPT-IR button is pressed, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

The WPT-IR can generate a Cancel or Secondary message by activating its built-in magnetic switch by swiping a magnet by its left side.

The WPT-IR can generate an automated message to report low battery status. In addition, the WPT-IR offers full wireless supervision from the main paging controller. This provides the system administrator with a detailed functionality status of each installed device.

The WPT-IR can be equipped with a "Man-Down" option that activates an automated message when the WPT-IR changes position from vertical to horizontal. This option is optimal for security applications.

This water-resistant pendant includes a belt clip and pendant necklace.

Key Features:

- Two Programmable Messages
- Sends Message Directly to a Pager
- Location ID Information (With Optional WPR-IR)
- 300 - 1,000 Foot Range (Can be Increased by Using a Data Repeater)
- Built-in Magnetic Cancel Switch
- Transmission Indicator
- Long-life Single Lithium Battery
- Low Battery Alert

Options, Accessories and Complementary Products:

Part Number	Description
WPR-IR	Infrared Location Transmitter
VSPS-03	Programming Kit
WPRP-2/WPRP-5	Data Repeater
Other	Man Down Sensor

Specifications:

Dimensions	2" x 2.3" x 0.9" (W x H x D)	Call Cancel	Internal Magnetic Switch
Weight	1.3 oz.	Signalling Time	2 - 4 Seconds
Power	Single 3V Lithium Battery	Stability	Better than 5 PPM
Color	Transparent Red	Frequency	467.8000 MHz (Additional Frequencies Available)
Operating Temperature	32° - 140°F	Paging Format	POCSAG, 512 or 1200 BPS
Humidity	0% - 90%, Non-Condensing	Channel Spacing	12.5 KHz - Narrow Band
RF Power	10 mW	Activation Codes	3 (Call, Cancel & Low Battery)
Programming	PC Based Programming Kit	Limited Warranty	One Year Parts and Labor

*Specifications Are Subject to Change Without Notification