



TS5241 - Wireless Synchronized Digital Clock



The **TS5241 Wireless Synchronized Digital Clock** is designed with a highly visible 2.5" LED four-digit display.


The TS5241 receives a wireless time signal transmitted daily by a main wireless paging controller, such as the **VS4800**. The TS5241 will use the time signal to automatically adjust itself, if necessary, to ensure accurate and synchronized time throughout the entire facility.

The TS5241 matches a wide variety of applications and provides years of maintenance-free service.

The TS5241 comes with a built-in battery backup.

Key Features:

- Viewing Distance of 100'
- Automatic Daylight Saving Time Adjustment
- Non-Glare Acrylic Lens
- Quick Correction for Time Change (1-3 Minutes)
- Flush Mount, Does Not Require Back Box
- AC Power Operated
- AM/PM Indicator



Options, Accessories and Complementary Products:

Part Number	Description
TS-OPT-010	Wireless Count Down Timer for Digital Clock
TS-ACC-002	Dual Face Bracket for Digital Clock - Wall Mount
TS-ACC-003	Dual Face Bracket for Digital Clock - Ceiling Mount

Specifications:

Dimensions	14.21" x 6.22" x 1.5" (W x H x D)	Digit Count, Size & Color	4 Digits, 2.5" High, Red
Weight	3.55 lbs.	Frequency	VHF (148 - 174 MHz), UHF (400 - 470 MHz)
Power	12V DC / 2A (Using 100-240V AC)	Paging Format	POCSAG, Narrow Band
Operating Temperature	17° - 140°F	Synchronization	Instantaneous
Humidity	0% - 95%, Non-Condensing	Receiver Sensitivity	10u V/M
Frame and Lens	Black Aluminum Frame, Red Diffused Acrylic Lens	Limited Warranty	One Year Parts and Labor
Viewing Distance	100 ft.		

*Specifications Are Subject to Change Without Notification