



TS5242 - Wireless Synchronized LCD Digital Clock



The **TS5242 Wireless Synchronized LCD Digital Clock** is designed with a highly visible 2.25" four-digit display.

The TS5242 receives a wireless time signal transmitted daily by a main wireless paging controller, such as the **VS4800**. The TS5242 uses the time signal to automatically adjust itself, if necessary, to ensure accurate and synchronized time throughout the entire facility.

The TS5242 matches a wide variety of applications and provides years of maintenance-free service.

The TS5242 is designed for desk or wall mounting.

Key Features:

- Viewing Distance of 50'
- Automatic Daylight Saving Time Adjustment
- Quick Correction for Time Change (1-5 Minutes)
- Flush Mount
- Desk or Wall Mount
- Battery Operated
- AM/PM Indicator

Specifications:

Dimensions	12" x 8.1" x 1.1" (W x H x D)	Digit Count, Size & Color	4 Digits, 2.25" High, Black
Weight	1.25 lbs.	Frequency	VHF (148 - 174 MHz), UHF (400 - 470 MHz)
Power	2 AA Batteries	Paging Format	POCSAG, Narrow Band
Operating Temperature	17° - 140°F	Synchronization	1 - 5 Minutes
Humidity	0% - 95%, Non-Condensing	Receiver Sensitivity	10u V/M
Frame and Lens	Plastic, Stainless Steel Finish	Limited Warranty	One Year Parts and Labor
Viewing Distance	50 ft.		

*Specifications Are Subject to Change Without Notification