



## VNS2268 - Wireless Two-Way Intercom Station



VNS2210

The VNS2268 Wireless Two-Way Intercom Station is designed to provide two-way communication for applications where the installation of traditional hard-wired intercom systems is impractical or too costly.

When the VNS2268 is used with a main wireless paging controller, such as the VS4500 or VS4810, two-way communication between the main paging controller and an intercom wall station (or emergency call box) becomes available. The main paging controller can also initiate one-way communication to a group of intercom wall stations.

The VNS2268 is controlled by the VNS2210 wireless audio/visual controller to provide simple, reliable and cost-effective alternative solutions to traditional wired intercom systems.

### Key Features:

- Hands Free Two-Way Communication
- One-Way PA Communication
- Integrated 4W Speaker
- Built-In Microphone with Gain Control

### Options, Accessories and Complementary Products:

| Part Number | Description                      |
|-------------|----------------------------------|
| VNS2200     | Wireless Audio/Visual Controller |
| VNS2210     | Wireless Audio/Visual Controller |

### Specifications:

|                       |   |                  |   |
|-----------------------|---|------------------|---|
| Dimensions            | 5.5" x 4" x 1.6"                                  | Data Cable       | 25', CAT-5  |
| Weight                | 0.8 lbs.  | Audio            | Built-In Omni-Directional Microphone and Speaker  |
| Material / Finish     | ABS Plastic, Black Faceplate with White Trim Ring | Operation Modes  | Main Paging Controller to Intercom Wall Station(s), Intercom Wall Station to Main Paging Controller, Main Paging Controller Monitoring Mode |
| Operating Temperature | 0° - 140°F  | Limited Warranty | One Year Parts and Labor  |

\*Specifications Are Subject to Change Without Notification

**VISIPLEX**

**877 918-7243**

[www.visiplex.com](http://www.visiplex.com)