



VP-N - Compact Numeric Pager



The **VP-N Compact Numeric Pager** is designed to accommodate a wide variety of paging applications.

The VP-N supports 4 activation codes (ID's) for individual activation or membership activation in 3 separate groups. Creating groups provides the ability to activate multiple devices using a single transmission from a main wireless paging controller, such as the **VS4800** or **VNS5100**.

The VP-N includes a built-in belt clip and a battery.

Key Features:

- 12 Digit Top Display
- Unread Message Reminder
- Low Battery Indication
- Adjustable LCD Contrast
- Backlight Display
- In-Range Indication
- Date and Time Display
- Vibrate and Tone Modes

Specifications:

| | | | |
|-----------------------|--------------------------------------|----------------------|--|
| Dimensions | 1.7" x 2.4" x 1.2" (W x H x D) | Selectivity | Better than 65 db |
| Weight | 1.6 oz. | Spurious Rejection | Better than 60 PPM |
| Power | One 1.5 V AAA Battery | Image Rejection | Better than 50 db |
| Color | Black | Stability | Better than 5 PPM |
| Operating Temperature | 14° - 130° F | Frequency | VHF (148 - 174 MHz), UHF (400 - 470 MHz) |
| Humidity | 0% - 95%, Non-Condensing | Paging Format | POCSAG, Narrow Band |
| Alert Level | Minimum 75 db | Data Baud Rate | 512 or 1200 BPS |
| Display Format | One Line with a 12 Digit Top Display | Receiver Sensitivity | 7u V/M |
| Activation Codes | 4 | Limited Warranty | One Year Parts and Labor |

*Specifications Are Subject to Change Without Notification

VISIPLEX

877 918-7243

www.visiplex.com