

# WPR Wireless POCSAG Receiver

*The Visiplex Wireless POCSAG Receiver series is designed to provide the perfect solution for applications that need remote control of appliance activity, reception of paging activity, and specific wireless messages to sign boards or computers. Each WPR receiver comes with an RS-232 interface and a relay dry contact output so controlling electrical devices activity could be simple as sending an On/Off page message.*

## WPR Wireless POCSAG Receiver

- Works like a regular POCSAG pager!
- Works in the VHF, UHF and 900MHz bands
- Fully programmable capcodes
- Built-in message controlled relay
- Integrated RS-232 interface
- Relay activation is password protected
- POCSAG signaling format
- Monitors all paging activity
- Provides wireless data link to Sign Boards
- Enables wireless control of Dome Lights
- Low power - can be battery operated



## Performance / Specifications:

Relay output	Dry contact output, capcode and message controlled
Signaling	POCSAG 512 - 2400BPS, Direct FM
Operating frequency	150-174MHz, 402-470 MHz & 906-930Mhz
Sensitivity	-101 dBm
Antenna	Built-In antenna
Interface	RS-232 interface 9600BPS
Mounting	Wall mount
Programming	PC software to program all capcodes & passwords
Overall size	3.00" W x 2.7" H x 1.25" D
Operating temp.	-10 to +45C
Operating power	9-12V DC 20mA
Weight	2.8 OZ.

## Visiplex Technologies, Inc.

111 Deer Lake Road, Suite 120  
Deerfield, IL 60015

Phone: (847) 405-0771 Fax: (847) 405-0776

E-mail: [sales@visiplex.com](mailto:sales@visiplex.com)

Web site: [www.visiplex.com](http://www.visiplex.com)

