



WPR-IR - Infrared Pendant Location Transmitter



WPT-IR

Key Features:

- Provides Location ID Information for WPT-IR Pendants
- Programmable Location ID
- Approximate 30' Radius (2,000 Square Feet)
- Ceiling or Wall Mount

The **WPR-IR Infrared Pendant Location Transmitter** is designed to provide location information to the WPT-IR pendants. When the WPT-IR button is pressed, it receives the Location ID information from a nearby WPR-IR. This ID is sent with the pre-programmed message to a designated pager or LED Display. When used with a main wireless paging controller, such as the **VNS5100**, the location ID can be converted to a customized description.

The pendant's activation code can be used to signal the main paging controller and generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

In this configuration, when the WPT-IR button is pressed, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

The WPR-IR unit is designed for ceiling or wall mounting.

Options, Accessories and Complementary Products:

Part Number	Description
WPT-IR	Wireless UHF Infrared Pendant Transmitter
Other	Man Down Sensor

Specifications:

Dimensions	4.25" x 2.25" (W x H)	Humidity	0% - 90%, Non-Condensing
Weight	1.6 lbs.	Transmit Range	Approximate 30 ft. Radius (2,000 Sq. Ft.)
Power	12V DC / 3A (Using 110-220V AC)	Packaging	Weather-Resistant Polycarbonate for Indoors/Outdoors
Color	Red	Limited Warranty	One Year Parts and Labor
Operating Temperature	32° - 120°F		

*Specifications Are Subject to Change Without Notification